§63.324

(3) The total sum calculated in paragraph (d) of this section is the yearly perchloroethylene consumption at the facility.

[58 FR 49376, Sept. 22, 1993, as amended at 71 FR 42745, July 27, 2006; 71 FR 55280, Sept. 21, 2006]

EFFECTIVE DATE NOTE: At 73 FR 17256, Apr. 1, 2008, §63.323 was amended by revising pargraphs (a)(1) introductory text, (a)(1)(ii), (b) introductory text and (c) introductory text, effective July 15, 2008. For the convenience of the user, the revised text is set forth as follows:

§ 63.323 Test methods and monitoring.

(a) * * *

(1) The owner or operator shall monitor on a weekly basis the parameters in either paragraph (a)(1)(i) or (ii) of this section.

* * * * *

The (ii) temperature of the airperchloroethylene gas-vapor stream on the outlet side of the refrigerated condenser on a dry-to-dry machine, dryer, or reclaimer with a temperature sensor to determine if it is equal to or less than 7.2 °C (45 °F) before the end of the cool-down or drying cycle while the gas-vapor stream is flowing through the condenser. The temperature sensor shall be used according to the manufacturer's instructions and shall be designed to measure a temperature of 7.2 °C (45 °F) to an accuracy of ±1.1 °C (±2 °F).

* * * * *

(b) When a carbon adsorber is used to comply with §63.322(a)(2) or exhaust is passed through a carbon adsorber immediately upon machine door opening to comply with §63.322(b)(3), the owner or operator shall measure the concentration of PCE in the exhaust of the carbon adsorber weekly with a colorimetric detector tube or PCE gas analyzer. The measurement shall be taken while the dry cleaning machine is venting to that carbon adsorber at the end of the last dry cleaning cycle prior to desorption of that carbon adsorber or removal of the activated carbon to determine that the PCE concentration in the exhaust is equal to or less than 100 parts per million by volume. The owner or operator shall:

* * * * * *

(c) If the air-PCE gas vapor stream is passed through a carbon adsorber prior to machine door opening to comply with \$63.322(b)(3), the owner or operator of an affected facility shall measure the concentration of PCE in the dry cleaning machine

drum at the end of the dry cleaning cycle weekly with a colorimetric detector tube or PCE gas analyzer to determine that the PCE concentration is equal to or less than 300 parts per million by volume. The owner or operator shall:

§63.324 Reporting and recordkeeping requirements.

- (a) Each owner or operator of a dry cleaning facility shall notify the Administrator or delegated State authority in writing within 270 calendar days after September 23, 1993 (i.e., June 18, 1994) and provide the following information:
- (1) The name and address of the owner or operator;
- (2) The address (that is, physical location) of the dry cleaning facility;
- (3) A brief description of the type of each dry cleaning machine at the dry cleaning facility;
- (4) Documentation as described in §63.323(d) of the yearly perchloroethylene consumption at the dry cleaning facility for the previous year to demonstrate applicability according to §63.320; or an estimation of perchloroethylene consumption for the previous year to estimate applicability with §63.320; and
- (5) A description of the type of control device(s) that will be used to achieve compliance with §63.322 (a) or (b) and whether the control device(s) is currently in use or will be purchased.
- (6) Documentation to demonstrate to the Administrator's satisfaction that each room enclosure used to meet the requirements of §63.322(a)(3) meets the requirements of §63.322(a)(3) (i) and (ii).
- (b) Each owner or operator of a dry cleaning facility shall submit to the Administrator or delegated State authority by registered mail on or before the 30th day following the compliance dates specified in §63.320 (b) or (c) or June 18, 1994, whichever is later, a notification of compliance status providing the following information and signed by a responsible official who shall certify its accuracy:
- (1) The yearly perchloroethylene solvent consumption limit based upon the yearly solvent consumption calculated according to §63.323(d);

Environmental Protection Agency

- (2) Whether or not they are in compliance with each applicable requirement of §63.322; and
- (3) All information contained in the statement is accurate and true.
- (c) Each owner or operator of an area source dry cleaning facility that exceeds the solvent consumption limit reported in paragraph (b) of this section shall submit to the Administrator or a delegated State authority by registered mail on or before the dates specified in §63.320 (f) or (i), a notification of compliance status providing the following information and signed by a responsible official who shall certify its accuracy:
- (1) The new yearly perchloroethylene solvent consumption limit based upon the yearly solvent consumption calculated according to §63.323(d);
- (2) Whether or not they are in compliance with each applicable requirement of §63.322; and
- (3) All information contained in the statement is accurate and true.
- (d) Each owner or operator of a dry cleaning facility shall keep receipts of perchloroethylene purchases and a log of the following information and maintain such information on site and show it upon request for a period of 5 years:
- (1) The volume of perchloroethylene purchased each month by the dry cleaning facility as recorded from perchloroethylene purchases; if no perchloroethylene is purchased during a given month then the owner or operator would enter zero gallons into the log;
- (2) The calculation and result of the yearly perchloroethylene consumption determined on the first day of each month as specified in §63.323(d);
- (3) The dates when the dry cleaning system components are inspected for leaks, as specified in §63.322(k), (1), or (0)(1), and the name or location of dry cleaning system components where leaks are detected;
- (4) The dates of repair and records of written or verbal orders for repair parts to demonstrate compliance with §63.322(m) and (n):
- (5) The date and temperature sensor monitoring results, as specified in §63.323 if a refrigerated condenser is used to comply with §63.322(a), (b), or (o); and

- (6) The date and monitoring results, as specified in §63.323, if a carbon adsorber is used to comply with §63.322(a)(2), (b)(3), or (o)(2).
- (e) Each owner or operator of a dry cleaning facility shall retain onsite a copy of the design specifications and the operating manuals for each dry cleaning system and each emission control device located at the dry cleaning facility.
- (f) Each owner or operator of a dry cleaning facility shall submit to the Administrator or delegated State authority by registered mail on or before July 28, 2008 a notification of compliance status providing the following information and signed by a responsible official who shall certify its accuracy:
- (1) The name and address of the owner or operator;
- (2) The address (that is, physical location) of the dry cleaning facility;
- (3) If they are located in a building with a residence(s), even if the residence is vacant at the time of this notification:
- (4) If they are located in a building with no other tenants, leased space, or owner occupants;
- (5) Whether they are a major or area source:
- (6) The yearly PCE solvent consumption based upon the yearly solvent consumption calculated according to §63.323(d);
- (7) Whether or not they are in compliance with each applicable requirement of \$63.322; and
- (8) All information contained in the statement is accurate and true.

[58 FR 49376, Sept. 22, 1993, as amended at 58 FR 66289, Dec. 20, 1993; 71 FR 42745, July 27, 2006]

EFFECTIVE DATE NOTE: At 73 FR 17257, Apr. 1, 2008, $\S 63.324$ was amended by revising paragraphs (d)(5) and (6), effective July 15, 2008. For the convenience of the user, the revised text is set forth as follows:

§ 63.324 Reporting and recordkeeping requirements.

* * * * *

- (d) * * *
- (5) The date and monitoring results (temperature sensor or pressure gauge), as specified in §63.323 if a refrigerated condenser is used to comply with §63.322(a), (b), or (o); and

§ 63.325

(6) The date and monitoring results, as specified in §63.323, if a carbon adsorber is used to comply with §63.322(a)(2), or (b)(3).

* * * * * *

§ 63.325 Determination of equivalent emission control technology.

- (a) Any person requesting that the use of certain equipment or procedures be considered equivalent to the requirements under §63.322 shall collect, verify, and submit to the Administrator the following information to show that the alternative achieves equivalent emission reductions:
- (1) Diagrams, as appropriate, illustrating the emission control technology, its operation and integration into or function with dry-to-dry machine(s) or transfer machine system(s) and their ancillary equipment during each portion of the normal dry cleaning cycle;
- (2) Information quantifying vented perchloroethylene emissions from the dry-to-dry machine(s) or transfer machine system(s) during each portion of the dry cleaning cycle with and without the use of the candidate emission control technology;
- (3) Information on solvent mileage achieved with and without the candidate emission control technology. Solvent mileage is the average weight of articles cleaned per volume of perchloroethylene used. Solvent mileage data must be of continuous duration for at least 1 year under the conditions of a typical dry cleaning operation. This information on solvent mileage must be accompanied by information on the design, configuration, operation, and maintenance of the specific dry cleaning system from which the solvent mileage information was obtained:
- (4) Identification of maintenance requirements and parameters to monitor to ensure proper operation and maintenance of the candidate emission control technology;
- (5) Explanation of why this information is considered accurate and representative of both the short-term and the long-term performance of the candidate emission control technology on the specific dry cleaning system examined:

- (6) Explanation of why this information can or cannot be extrapolated to dry cleaning systems other than the specific system(s) examined; and
- (7) Information on the cross-media impacts (to water and solid waste) of the candidate emission control technology and demonstration that the cross-media impacts are less than or equal to the cross-media impacts of a refrigerated condenser.
- (b) For the purpose of determining equivalency to control equipment required under §63.322, the Administrator will evaluate the petition to determine whether equivalent control of perchloroethylene emissions has been adequately demonstrated.
- (c) Where the Administrator determines that certain equipment and procedures may be equivalent, the Administrator will publish a notice in the FEDERAL REGISTER proposing to consider this equipment or these procedures as equivalent. After notice and opportunity for public hearing, the Administrator will publish the final determination of equivalency in the FEDERAL REGISTER.

§ 63.326 Implementation and enforcement.

- (a) This subpart can be implemented and enforced by the U.S. EPA, or a delegated authority such as the applicable State, local, or Tribal agency. If the U.S. EPA Administrator has delegated authority to a State, local, or Tribal agency, then that agency, in addition to the U.S. EPA, has the authority to implement and enforce this subpart. Contact the applicable U.S. EPA Regional Office to find out if implementation and enforcement of this subpart is delegated to a State, local, or Tribal agency.
- (b) In delegating implementation and enforcement authority of this subpart to a State, local, or Tribal agency under subpart E of this part, the authorities contained in paragraph (c) of this section are retained by the Administrator of U.S. EPA and cannot be transferred to the State, local, or Tribal agency.
- (c) The authorities that cannot be delegated to State, local, or Tribal agencies are as specified in paragraphs (c)(1) through (4) of this section.